


LEAD FINISH: GOLD	
CASING FINISH: GOLD	
CAPACITANCE	1200pF +100%-0%
TEMP. RANGE	-55°C TO 125°C
CURRENT	5 AMP MAX.
WORKING VOLTAGE	125°C 200VDC MAX.
D.C. RESISTANCE	.01ohms MAX.

SCHEMATIC



MARKING:


NONE

PACKING:

BAG: SCI-9925-122
DATE CODE
LOT NO.
QTY./BAG (200 MAX.)

NOTES:

- SUGGESTED MOUNTING HOLE $\phi.132 \pm .002$
- MAX. SOLDERING TEMP 260°C FOR 20 SEC MAX

	2	1	0	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 ERIE, FAIRVIEW PENNSYLVANIA SPECTRUM CONTROL INC.	
	CN 22042-CPD	CN 205907	CN 186828	CHANGE NOTICE	Fractions $\pm 1/64$		Dwn. SLAGLE
					Dec. .xx \pm		Ckd. 2/14/02
					Dec. .xxx $\pm .005$		Apvd.
					Angles $\pm 0^{\circ} 30'$		THIRD ANGLE PROJECTION
					CODE IDENT. NO. DLSP2	Description FEEDTHRU FILTER SCI-9925-122	

